



# 66 -- Tabletip X-Ray Microtomography System

- Combine Synopsis/Solicitation Posted on May 12, 2006
- Amendment to Combined Synopsis/Solicitation 01 Posted on May 12, 2006

#### **General Information**

Document Type: Amendment to Combined Synopsis/Solicitation

Solicitation Number: N00173-06-R-JK03

Posted Date: Jun 22, 2006 Original Response Date: Jun 12, 2006 Current Response Date: Jul 07, 2006 Original Archive Date: Jun 22, 2007 Current Archive Date: Jun 22, 2007

Classification Code: 66 -- Instruments & laboratory equipment

Naics Code: 423490 -- Other Professional Equipment and Supplies Merchant

Wholesalers

### **Contracting Office Address**

Department of the Navy, Office of Naval Research, Naval Research Laboratory, 4555 Overlook Ave. S.W., Washington, DC, 20375

### **Description**

The purpose of this amendment is to reestablish a new closing date and to revise the specifications.

- 1.) The hour and date specified for receipt of offers is extended to July 7, 2006.
- 2.) The specifications previously provided are deleted in their entirety and replaced with the

following:

Specifications for a Table-top X-ray Microtomography Unit (Revised 6/22/06)

The x-ray computed microtomography unit, hereafter called the XCMT unit, must be able to scan an object and output a computer file, in a standard format, which contains three dimensional absorption contrast information concerning the object's internal microstructure.

The following minimum requirements are necessary.

- 1.) Materials: Scannable objects may be made from metals, plastics, ceramics, glasses, organic materials, geologic materials, or combinations thereof.
- 2.) Maximum Scannable Object Size: must be 38 mm or greater.
- 3.) X-ray Source: air-cooled, sealed micro-focus x-ray tube, 100kiloVolts (kV) Acceleration voltage, > 10,000 hours lifetime.
- 4.) X-ray Spot Size: < 5 microns at 4W, 20-100kV, 0-250 micro-Amps.
- 5.) Object Magnification: XCMT will be equipped with adjustable source to camera distance which provides selectable magnifications
- 6.) X-ray Detector: minimum 1024X1024 lens coupled camera.
- 7.) X-ray Filtering: capability of having up to three or more interchangeable x-ray filters for beam-hardening compensation and multi-energy scanning.
- 8.) Effective Pixel Size at Max. Magnification: minimum 1.6 microns or smaller.
- 9.) Low Contract Resolution: minimum 5 microns.
- 10.) Computer: minimum dual processor workstation with hard drive storage, DVD writer, monitor, mouse, keyboard, capable of image capture, with all required software necessary for volume reconstruction and volume rendering.
- 11.) Reconstruction Algorithms: Both back-projection for fan-beam, and cone-beam algorithms must be provided. Correction for beam hardening must be available. Network volume reconstruction must be available.
- 12.) Radiation Safety: <1 micro Sievert/hour or better at any point on the instrument surface.
- 13.) Electrical Utilities: 100-130 V AC, 4 A.
- 14.) Mechanical Testing: Unit must contain compression, tension and torsion stages for testing samples in situ.

15.) Software interface and controller for controlling mechanical test apparatu.

### **Point of Contact**

Janiece Shall, Contract Specialist, Phone 202-767-3710, Fax 202-767-0430, Email janiece.shall@nrl.navy.mil - F. Janilea Bays, Contracting Officer, Phone 202-767-2974, Fax 202-767-0430, Email jan.bays@nrl.navy.mil

### **Place of Performance**

Address: Naval Research Laboratory 4555 Overlook Ave. SW Washington, DC 20375

Register to Receive Notification

## **Government-wide Numbered Notes**

You may return to Business Opportunities at:

- DON ONR listed by [Posted Date]
- DON Agencywide listed by [Posted Date]

[Home] [SEARCH synopses] [Procurement Reference Library]